Wall & Door Guard



Figure 1: Wall & Door Guard positioned over an industrial high-speed overhead door.

The Wall & Door Guard provides necessary protection from damage to industrial door frames and high speed industrial doors. The yellow steel frame provides high visibility and PVC "Banger Bar" alerts operators of overhead clearance. The Wall & Door Guard also helps reduce repair costs.

Design Highlights

- Protects industrial speed overhead doors, door frames, walls, overhead conveyors and racking
- Lower PVC "Banger Bar" alerts operator of overhead clearance
- Powder-coated safety yellow for durability and high visibility
- This product carries a (1) year limited warranty with APS Resource

Technical Specifications		
Available Sizes	Adjustable to fit the width and height required for installation	
Construction Material	Heavy-duty welded steel	

P/N	Helght Workling Range	Width Working Range	Clearance Height Required
WDG8	7'6" to 8'6"	7'6" to 8'6"	9' - 1 5/8"
WDG10	9'6" to 10'6"	9'6" to 10'6"	11' - 1 5/8"
WDG12	11'6" to 12'6"	11'6" to 12'6"	13' - 1 5/8"
WDG16	15'6" to 16'6"	15'6" to 16'6"	17' - 1 5/8"

		Job Name
47)	lon	Address
9		General Contractor
<u> </u>	Jrinn.	Distributor
	olfo	Model
	=	Job NameAddress
<u></u>	on S	
2	Ħ	Ву
<u>ত</u>	775	
(ab)	2	Company
IIIe	etruc	Company
rtiffie	nstruc	CompanyAddress
Sertiffe	onstruc	Quantity By Company Address Date